

Installation Instructions

Eibach Springs, Inc. • 264 Mariah Circle • Corona, California 92879-1751 • USA • Tech Support 800-222-8811 Ext 114



Anti-Roll-Kit # 7713.312

Subaru, WRX STi, 2004 - 2007

Kit Contents	Description	Part Number	Qty
	Rear Bar	7713.320R	1
	Anti-Roll Hardware Kit	7713.312HK	1
	Bushing	UB0181	2
	Information Kit	EPAK	1
	Instructions	7713.312INST	1

NOTES: Read All Instructions Before Beginning Installation

- Only qualified mechanics experienced in the installation and removal of suspension components should perform this installation.
- Use of a hoist and screw jack is highly recommended and will substantially reduce installation time.
- **Installation time:** Is approximate 2 hours with the use of a hoist.
- **Never work on or under a vehicle unless it is properly supported.**
- **Tire Rotation:** In order to increase the life of your tires, it is recommended to rotate your tires every 3,000 miles.

Additional Eibach Components Available For Your Car

Eibach Kits	Part Number	Description	Front	Rear
<i>Pro-Kit</i>	7713.140	High Performance Handling	1.0 In.	.8 In.

FACTORY REAR BAR REMOVAL




Photo 1

1. Remove the bolt and nut that secures the bushing brackets, then, remove the brackets. (See Photo 1)



Photo 2

2. Remove the end links from the sway bar ends. (See Photo 2)
3. Remove the OE sway bar.

EIBACH REAR BAR INSTALLATION

1. Lube the new urethane bushings with the provided lube
2. Install the bushings onto the Eibach anti-roll bar.




Photo 3

3. Install the Eibach bar using the OE bushing brackets and reconnect the OE end links. (See Photo 3)

TUNING YOUR EIBACH BARS

- a) 1st hole / Softest Setting.
 - Reduces over-steer
 - Use in rain or on slick roads.
 - Use on rough or bumpy roads.
 - Increases comfort.
- b) 2nd hole / Firmest Setting.
 - Reduces under-steer
 - Use on dry roads and tracks.
 - Use on smooth roads and tracks.
 - Do not use on wet or slick roads.

