Installation Instructions



Eibach Springs, Inc. • 264 Mariah Circle • Corona, California 92879-1751 • USA • Tech Support 800-222-8811 Ext 114

Anti-Roll-Kit # 5536.310

Mazda, MX-5 2006-2007

Kit Contents	Description	Part Number	Qty
	Front Bar	5536.320F	1
	Front Anti-Roll Hardware Kit	5536.310HK	1
	Front Bushing	UB0124	2
	Lubricant	AR.LUBRICANT	1
	Information Kit	EPAK	1
	Instructions	5536.310INST	1

NOTES:

Read All Instructions Before Beginning Installation

- Only qualified mechanics experienced in the installation and removal of suspension components should perform this installation.
- **Use** of a hoist and screw jack is highly recommended and will substantially reduce installation time.
- Installation time: Is approximate .5 hour with the use of a hoist.
- Never work on or under a vehicle unless it is properly supported.
- **Tire Rotation:** In order to increase the life of your tires, it is recommended to rotate your tires every 3,000 miles.

Additional Eibach Components Available For Your Car

Eibach Kits	Part Number	Description	Front	Rear
Pro- Kit	5536.140	High Performance Handling	1.0 ln.	1.0 ln.
Sportline	4.3655	High Performance Handling	2.0 In.	2.0 In.

FACTORY FRONT BAR REMOVAL

- 1. With the vehicle safely supported, remove all 4 wheels.
- 2. Locate the OE end links and remove the 14mm nuts fastening the end links to the anti-Roll bar. See Photo 1.



Photo 1

3. Locate the Anti-Roll bar bushing brackets. They are fastened to the frame with three 14mm bolts and one 14mm nuts. See photo 2.





4. Now you must slowly remove the bar out through the drivers side. (Note: Be careful during this step because there are some water and power steering lines near by.)

EIBACH FRONT BAR INSTALLATION

- 1. The new Eibach front bar can be installed in the reverse order.
- 2. Apply the supplied lubricant to the inside of the new front bushings (Part # UB0124). Install the bushing on to the bar new Eibach with the "cut" portion toward the rear of the vehicle.
- 3. Install your new Eibach Anti-Roll bar in the reverse order of removal.