## Installation Instructions

Eibach Springs, Inc. • 264 Mariah Circle • Corona, California 92879-1751 • USA • Tech Support 800-222-8811 Ext 114



## Pro-Kit # 7721.140

2009+ Subaru WRX, 4 & 5 Door, 2.5L Turbo H4, Exc. STi

Kit Contents	Description	Part Number	Qty	
	Front Spring	7721.001	2	
	Rear Spring	7721.002	2	
	Information Kit	EPAK	1	
	Instructions	7721.140INST	1	

## NOTES: Read All Instructions Before Beginning Installation

- Installation of a *Pro-Kit* Spring set should only be performed by a qualified mechanic experienced in the installation and removal of suspension springs.
- Use of a hoist is highly recommended and will substantially reduce installation time.
- Never work on or under a vehicle unless it is properly supported by safety stands and wheels are blocked.
- **Pro-Kit** Springs are marked with an **001** and an **002** (located at the end of the part number) designating front and rear springs.
- **Pro-Kit** Springs should be installed with the **Eibach** Logo right side up. All original stock spring isolators, dampers and tubing should be retained from the stock springs and used when installing the **Pro-Kit** Springs.
- After installation, it is always important to inspect and adjust the following if necessary:
  - Wheel alignment such as camber, caster & toe.
  - Tire and/or wheel fender clearance.
  - Brake line clearance and attachments.
  - Brake anti-locking and anti-skid system sensors.
- Tire Rotation: In order to increase the life of your tires, it is recommended to rotate your tires every 3,000 miles.
- For MacPherson Strut Type front suspension, it is important to mark the upper perch with respect to the lower perch before disassembly. This orientation must remain the same with the installation of the Pro Kit Springs. Noise may result if this procedure is not performed correctly

**ALIGNMENT:** After installation, it will be necessary to perform a full vehicle alignment using factory specifications.

