

# Installation Instructions

Eibach Springs, Inc. • 264 Mariah Circle • Corona, California 92879-1751 • USA • Tech Support 800-222-8811 Ext 114



## PRO-KIT- # 4.6082

Lexus – IS300, Incl Sport Cross 4/99 - 2005

Kit Contents	Description	Part Number	Qty
	Front Spring	4.6082F	2
	Rear Spring	4.6082R	2
	Front Bumpstop	770051	2
	Rear Bumpstop	770052	2
	Information Kit	EPAK	1
	Instructions	4.6082INST	1

### NOTES: Read All Instructions Before Beginning Installation

- Installation of a **SPORTLINE** Spring set should only be performed by a qualified mechanic experienced in the installation and removal of suspension springs.
- Use of a hoist is highly recommended and will substantially reduce installation time.
- **Never work on or under a vehicle unless it is properly supported by safety stands and wheels are blocked.**
- **SPORTLINE** Springs are marked with **F** and **R** (located at the end of the part number) designating front and rear springs.
- **SPORTLINE** Springs should be installed with the **Eibach** Logo right side up. All original stock spring isolators, dampers and tubing should be retained from the stock springs and used when installing the **SPORTLINE** Springs.
- **After** installation, it is always important to inspect and adjust the following if necessary:
  - Wheel alignment such as camber, caster & toe.
  - Tire and/or wheel fender clearance.
  - Brake line clearance and attachments.
  - Brake anti-locking and anti-skid system sensors.
- **Tire Rotation:** In order to increase the life of your tires, it is recommended to rotate your tires every 3,000 miles.

### ALIGNMENT:

After installation, it will be necessary to perform a full vehicle alignment using factory specifications.

### Bump Stop Instructions

Typical Bump-Stop  
(Bump-Stop from your vehicle may have different shape)

