

Installation Instructions

Eibach Springs, Inc. • 264 Mariah Circle • Corona, California 92879-1751 • USA • Tech Support 800-222-8811 Ext 114



SPORTLINE Kit – #4.1740

HONDA, Civic, 2-door & 4-door (Incl. Hatchback), 4 Cyl; 1992-2000

HONDA, Civic Si, 4 Cyl; 1999-2000

HONDA, Del Sol, 4 Cyl; 1993-1997

Kit Contents	Description	Part Number	Qty
	Front Spring	4.1740F	2
	Rear Spring	4.1740R	2
	Information Kit	EPAK	1
	Instructions	4.1740INST	1

NOTES: Read All Instructions Before Beginning Installation

- Installation of a **SPORTLINE** Spring set should only be performed by a qualified mechanic experienced in the installation and removal of suspension springs.
- Use of a hoist is highly recommended and will substantially reduce installation time.
- **Never work on or under a vehicle unless it is properly supported by safety stands and wheels are blocked.**
- **SPORTLINE** Springs are marked with the letter F and R (located at the end of the part number) designating front and rear springs.
- **SPORTLINE** Springs should be installed with the **Eibach** Logo right side up. All original stock spring isolators, dampers and tubing should be retained from the stock springs and used when installing the **SPORTLINE** Springs.
- **After** installation, it is always important to inspect and adjust the following if necessary:
 - Wheel alignment such as camber, caster & toe
 - Tire and/or wheel fender clearance
 - Brake line clearance and attachments
 - Brake anti-locking and anti-skid system sensors
- **Tire Rotation:** In order to increase the life of your tires, it is recommended to rotate your tires every 3,000 miles.

ALIGNMENT:

After installation, it will be necessary to perform a full vehicle alignment. **Eibach** offers the following alignment kits for this vehicle:

Part #: 5.84560K	Front/ Rear: Rear	Camber Adjustment: +/-0.25 °
Part #: 5.84580K	Front/ Rear: Rear	Camber Adjustment: +/-0.75 °
Part #: 5.84945K	Front/ Rear: Front	Camber Adjustment: +0-1.25 °

Bump Stop Trimming Instructions

Typical Bump-Stop
(Bump-Stop from your vehicle may have different shape)

