

Installation Instructions

Eibach Springs, Inc. • 264 Mariah Circle • Corona, California 92879-1751 • USA • Tech Support 800-222-8811 Ext 114



PRO-KIT # 4018.140

Honda, Civic 2&4-door (Incl. EX, DX, HX, LX, Si & Hatchback Models) 1996-2000

Kit Contents	Description	Part Number	Qty
	Front Spring	4018.001	2
	Rear Spring	4017.002	2
	Information Kit	EPAK	1
	Instructions	4018.140INST	1

NOTES: Read All Instructions Before Beginning Installation

- **Only qualified mechanics experienced in the installation and removal of suspension components should perform this installation.**
- **Use** of a hoist is highly recommended and will substantially reduce installation time.
- **Never work on or under a vehicle unless it is properly supported by safety stands and wheels are blocked.**
- **PRO-KIT** springs are marked with a .001, for Front and .002, for the Rear.
- **PRO-KIT** springs should be installed with the Eibach Logo right side up. All original stock spring isolators, dampers and tubing should be retained from the stock springs and used when installing the **PRO-KIT** Springs.
- **After** installation, it is always important to inspect and adjust the following if necessary:
 - Wheel alignment such as camber, caster & toe
 - Tire and/or wheel fender clearance, when aftermarket tires and wheels are used.
 - Brake line clearance and attachments
 - Brake anti-locking and anti-skid system sensors
- **Tire Rotation:** In order to increase the life of your tires, it is recommended to rotate your tires every 3,000 miles.

ALIGNMENT:

After installation, it will be necessary to perform a full vehicle alignment. Eibach offers the following alignment kits for this vehicle.

Part #: 5.84560K

Front/ Rear: Rear

Camber Adjustment: +/-0.25

Part #: 5.84580K

Front/ Rear: Rear

Camber Adjustment: +/-0.75

Part #: 6.13100K

Front/ Rear: Front

Camber Adjustment: +1.0-3.0

Bump Stop Trimming Instructions

Typical Bump-Stop

(Bump-Stop from your vehicle may have different shape)

