

# Installation Instructions

Eibach Springs, Inc. • 264 Mariah Circle • Corona, California 92879-1751 • USA • Tech Support 800-222-8811 Ext 114



## PRO-KIT # 85109.140

2010 Volkswagen GTI, 5K, 2.0 TFSI

2012-13 Volkswagen Jetta GLI, 2.0L 4 Cyl. Turbo

Kit Contents	Description	Part Number	Qty
	Front Spring	85109.001	2
	Rear Spring	85109.002	2
	Front Bump Stop	BS45008620	2
	Rear Bump Stop	BS770060	2
	Rear Dust Boot	BS770043	2
	Information Kit	EPAK	1
	Instructions	85109.140INST	1

### NOTES: Read All Instructions Before Beginning Installation

- **Only qualified mechanics experienced in the installation and removal of suspension components should perform this installation.**
- **Use** of a hoist is highly recommended and will substantially reduce installation time.
- **Never work on or under a vehicle unless it is properly supported by safety stands and wheels are blocked.**
- **PRO-KIT** springs are marked with a .001, for Front and .002, for the Rear.
- **PRO-KIT** springs should be installed with the Eibach Logo right side up. All original stock spring isolators, dampers and tubing should be retained from the stock springs and used when installing the **PRO-KIT** Springs.
- **After** installation, it is always important to inspect and adjust the following if necessary:
  - Wheel alignment such as camber, caster & toe
  - Tire and/or wheel fender clearance, when aftermarket tires and wheels are used.
  - Brake line clearance and attachments
  - Brake anti-locking and anti-skid system sensors
- **Tire Rotation:** In order to increase the life of your tires, it is recommended to rotate your tires every 3,000 miles.
- **For MacPherson Strut type front suspension,** it is important to mark the orientation of the upper perch with respect to the lower perch before disassembly. This orientation must remain the same with the installation of the Pro Kit springs. Noise may result if this procedure is not performed correctly.

Eibach Kits	Part Number	Description	Front	Rear
<i>Anti-Roll Kit</i>	8598.320	Performance Tuned Lowering	26mmSA	23mmSA

### Bump Stop Modification Instructions

Typical Bump-Stop

(Bump-Stop from your vehicle may have different shape)

